

OAK BOULES



STAIRCASE GRADE:

thickness: 27, 42, 52, 65, 80 mm diameter: 55 cm and wider

length: 3m50 and longer, mostly 4m00 / +

FURNITURE GRADE:

thickness: 20, 27, 32, 42, 52 mm width: 40 / 45 cm and wider length: 3m50 and longer

Debarked, dried profiled sticks, replaced to avoid sticker marks, air drying under roof with ventilation.



WE CONDITION AND DRY YOUR WOOD:

All wood is properly stacked on big pallets (50 tons) to AIR dry in the wind and then KILN dry in our kilns.

A unique internal transport system moves these pallets quickly to the desired zone: fast drying zone / slow drying zone / protected zone / kilns ...

We determine the right place in function of the weather conditions, the type of wood, the thickness and the moisture content.

We dry maximally in the wind, but can control by moving the pallets, to avoid cracks in dry periods and discolorations in humid periods.

We strive to put the wood only in the drying kiln, when the fiber saturation point is reached. This gives optimal results both for the physical properties of the dried wood and in terms of cost.

All wood is stacked under roof, protected from wind, sun and rain.

This way of working is very ECO-friendly and delivers the best conditions to dry your wood.

STOCK:

With a permanent stock of more than 4000 m3 boules in Beech and Oak DB Hardwoods can assure a consistent quality and a short delivery time (max 1 week).

V.20.1









SQUARE EDGED



SQUARE EDGED:

quality: mix grade QF2 and better thickness: 27, 42 and 52 mm width: 100 mm and wider long lengths: 1m80 - 4m00

FLOORING:

quality: good rustic thickness: 27 mm width: 210 mm length: 2m00 - 4m00

OAK BEAMS & CONSTRUCTION WOOD:

Always more than 1000 m3 beams in French Oak in stock, more information on our site or in our specific brochure.









